

### **Product technical sheet**

### **PRB 113**







5+

28 kids

61,5 m<sup>2</sup>





### **Material specification**

- Construction made of Robinia very durable acacia wood with a diameter of ~ 18 cm without sharp edges, resistant to weather conditions,
- Platforms made of Robinia very durable acacia wood, resistant to weather conditions,
- · Steps made of anti-slip and waterproof HPL plate,
- Roofs made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- Side panels made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- Slides made of stainless steel,
- · Windows made of HPL plate resistant to weather conditions,
- Climbing stones made of durable HPL plate, resistant to weather conditions, and stainless steel,
- Steel ropes in polypropylene braid, connected with durable aluminum, stainless steel and/or plastic elements,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- · Calibrated stainless steel chains, preventing fingers entrapment,
- Stainless steel bars,
- Stainless steel screws and/or screws covered with plastic caps,
- Stainless steel screws,



#### Physical development



balance

passage



sliding



climbing

KUCE RAKİCA BR7 TUZİ / MONTENEGRO +382 69 226 334

+382 69 226 337

+382 67 190 090

INFO@PARKWORLDMNE.COM OFFICE@PARKWORLDMNE.COM









# PRB 113

#### **Product data**


Length	680 cm
Width	680 cm
Total height	355 cm
Age group	5+ years
Number of users	28 kids
Safety zone	61,5 m2
Free fall height	238 cm
The height of the platforms	120 cm
In accordance with norm EN	1176-1:2017
Weight of the heaviest part	90 kg
Dimensions of the largest part	390x18x18 cm
Availability of spare parts	YES
Installation time	8,0 h


Data is subject to change without prior notice.


### **Additional information**

- · equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 100/80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;











### Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
bark (A,C)	Particle size from 20	30	≤200
	to 80	40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		238

## Amount of safe surface corresponding with free fall

**PRB 113** 

height:

HIC 64	9,8 m <sup>2</sup>	
HIC 85	7,8 m²	
HIC 100	5,1 m²	
HIC 120	9,3 m²	40
HIC 147	1,2 m²	
HIC 170	6,5 m²	
HIC 175	1,4 m²	-50
HIC 189	1,9 m²	
HIC 238	18,5 m²	

Data is subject to change without prior notice.

