

### **Product technical sheet**

# **PRB 123**







3+

20 kids

49,3 m<sup>2</sup>





- Construction made of Robinia very durable acacia wood with a diameter of ~ 18 cm without sharp edges, resistant to weather conditions,
- Platforms made of Robinia very durable acacia wood, resistant to weather conditions,
- Steps made of anti-slip and waterproof HPL plate,
- Side panels made of Robinia very durable acacia wood without sharp edges, resistant to weather conditions
- · Slides made of stainless steel,
- Telescope made of stainless steel and durable HDPE plate, resistant to weather conditions,
- Flags / sails made of durable HPL plate, resistant to weather conditions,
- · Rudder made of durable HDPE plate, resistant to weather conditions,
- Elements made of durable HPL plate, resistant to weather conditions,
- Steel ropes in polypropylene braid, connected with durable aluminum, stainless steel and/or plastic elements,
- Ladders made of steel ropes in polypropylene braid and rungs made of synthetic material,
- · Calibrated stainless steel chains, preventing fingers entrapment,
- · Screws covered with plastic caps and/or stainless steel screws,



#### Intellectual development



manipulation



sight



#### **Physical development**



balance



hiding



sliding



passage

KUCE RAKİCA BR7 TUZİ / MONTENEGRO +382 69 226 334

+382 69 226 337

+382 67 190 090


INFO@PARKWORLDMNE.COM OFFICE@PARKWORLDMNE.COM



















## **Product technical sheet**

# **PRB 123**

#### **Product data**

Length	820 cm	
Width	340 cm	
Total height	400 cm	
Age group	3+ years	
Number of users	20 kids	
Safety zone	49,3 m2	
Free fall height	90 cm	
The height of the platforms	55, 90 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	115 kg	
Dimensions of the largest part	500x18x18 cm	
Availability of spare parts	YES	
Installation time	10,5 h	

Data is subject to change without prior notice.

#### Additional information

- · equipment intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jamming the head, fingers or any other body parts;
- anchoring on flat surface, 100/80/70/60 cm deep;
- slide should not be installed southwards;
- render is for reference only, the actual appearance of the equipment and its color may vary;



## Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	÷.	≤100
bark (A,C)	Particle size from 20 to 80	30	≤200
		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		100

## **Product technical sheet**

# **PRB 123**

# Amount of safe surface corresponding with free fall height:

HIC <60	23,5 m <sup>2</sup>	
HIC 90	17,2 m <sup>2</sup>	
HIC 100	8,6 m <sup>2</sup>	- 18. 26.

Data is subject to change without prior notice.

